

COMPACT



A3 Tactical's Compact Shorty Vertical Grip is the perfect foregrip for limited-space rails. The unique integration of forward Hand-stop and Vertical Foregrip in such a short combo opens up applications that previously were not possible.

The system is completely modular, allowing it to be setup with multiple grip configurations. Our short grips and mid-length "Grenade" style grips are ideal for CQC or any application where a minimalist grip is necessary.

- OA Length on rail - M-LOK: 2.525"
- OA Length on rail - KEYMOD: 2.525"
- OA Length on rail - PICATINNY: 2.25"



M-LOK

1. Loosen the screws on your VFG with a 1/8 Allen wrench. The M-LOK nut should have a gap slightly larger than the thickness of your handguard.
2. Position the VFG base to the desired position on the handguard, inserting the nuts into the appropriate M-LOK slots.
3. Turn the screw until the M-LOK nut rotates 90 degrees from the slot orientation. This should lock the VFG to the rail.
4. Once "locked", tighten the (2) screws.



PICATINNY

Your A3 Tactical Picatinny VFG locks onto the rail using a unique tensioned insert. This method of attachment is the most secure Picatinny mounting solution available.

1. Slide VFG base onto rail and determine the desired mounting position.
2. There are two sets of holes on your VFG. Only 2 are necessary to lock your VFG into place. Determine which set of holes align with an open slot on the handguard. Slide the provided insert into this slot as shown in the image above.
3. Position the VFG back into position, aligning the set screws over the installed insert.
4. Tighten screws against the insert, locking down the VFG.
5. Once the base is secure, thread on your vertical grip.
6. Should the firearm to verify position and comfort. Re-position if necessary.



ALL NFA RULES APPLY. It is up to the user to ensure that installing this product does not violate any rules set forth by BATF concerning NFA requirements.